

13.3" LED Specifications



Key Features

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- Wide Temp. Range (-20 C~60 C)
- High Uniformity (90%)
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- Life Expectancy (70,000hrs)



DLF/DLH1315

Model No.	DLF1315	DLH1315
LCD Display	13.3" LED Backlight LCD	
Display Area	286.08 x 178.8mm	
Brightness	1000 cd/m ²	
Resolution	1280 x 800 (WXGA)	
Contrast Ratio	500 : 1	
Pixel Pitch (mm)	0.2235(H) x 0.2235(V)	
Viewing Angle	+70 ~-70 (H), +60 ~-60 (V)	
Display Color	262K	
Response Time	16ms (Typical)	
Sync	LVDS	
Power Consumption	7.5W	12.5W
LED Driving Board	LI D12A	
Control Board (Optional)	AD5621GA AD5621GD AD5766GDVA	
F / R Control Button	5 Key 4 Key	
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....	
Dimensions (WxHxD)mm	299x195x7.7	299x195x7.7
Weight	752g	852g
Optional	AOT Touch Waterproof	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA
AD5621GA	VGA+Audio
AD5621GD	VGA+DVI
AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
F / R Control Button	5 Key / 4 Key (Optional)
5 Key	Power Switch, Menu, Select (+,-), Auto
4 Key	Power Switch, Menu, Select (+,-)



Product Inquiries to:
 Flat Panel Display Solutions LLC.
 info@FPDSolutions.com
 skype: sunlight.fpd
 Phone: 503-992-1242

Premium Optical Lamination of Clear and Matte Anti-Reflection Film
 Optical Bonding AR and AG Glass, Touch Panels, Optical Filters and Shields
 US Value Add, Warranty, and Support
 Polarizer and Backlight Repair
 Display Optimization and Contract Assembly
 Consulting and Design Guidance