

15" LED Specifications



Key Features

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- Wide Temp. Range (-20 C~60 C)
- High Uniformity (90%)
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- Life Expectancy (70,000hrs)



DLF/DLH1564/1568

Model No.	DLF1564/68	DLH1564/68
LCD Display	15" TFT LCD Module	
Display Area	304.128 x 228.096 mm	
Brightness	800 cd/m ² /1600 cd/m ²	
Resolution	1024x768 (XGA)	
Contrast Ratio	600 : 1	
Pixel Pitch (mm)	0.297(H) x 0.297(V)	
Viewing Angle	+80 ~-80 (H), +80 ~-80 (V)	
Display Color	16.7M	
Response Time	8ms (Typical)	
Sync	LVDS	
Power Consumption	TBA/15.6W	TBA/21W
LED Driving Board	LI 1215A	
Control Board (Optional)	AD5621GA AD5621GD AD5766GDVA	
F / R Control Button	5 Key 4 Key	
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....	
Dimensions (WxHxD)mm	326.5x253.5x11.13	326.5x253.5x11.13
Weight	1.5kg	1.5kg
Optional	AOT Touch	Waterproof
<i>Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.</i>		
Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA	
AD5621GA	VGA+Audio	
AD5621GD	VGA+DVI	
AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)	
F / R Control Button	5 Key / 4 Key (Optional)	
5 Key	Power Switch, Menu, Select (+,-), Auto	
4 Key	Power Switch, Menu, Select (+,-)	



Product Inquiries to:
Flat Panel Display Solutions LLC.
 info@FPDSolutions.com
 skype: sunlight.fpd
 Phone: 503-992-1242

Premium Optical Lamination of Clear and Matte Anti-Reflection Film
 Optical Bonding AR and AG Glass, Touch Panels, Optical Filters and Shields
 US Value Add, Warranty, and Support
 Polarizer and Backlight Repair
 Display Optimization and Contract Assembly
 Consulting and Design Guidance

Your Industrial Solutions Partner!